

**SEMPERIT** 



## FLEXLINE 5000





Высокогибкий мультиспиральный компактный гидравлический шланг с уменьшенным радиусом изгиба и уменьшенным сопротивлением изгибу, отвечает стандарту ISO 18752 - CCT



### РУКАВ :

<b>Внутренний слой</b>	Синтетический каучук, стойкий к гидравлическим жидкостям (HL, HLP, HLPD, HVLP, HFA, HFAS, HFB, HFC)
<b>Усиление</b>	Четыре стальные проволочные навивки высокой прочности
<b>Наружный слой</b>	Стойкий к воздействию абразивов и погодных условий синтетический каучук <b>Внимание:</b> покрытие MSHA и SemperRock доступны
<b>Рабочая температура</b>	-40° C до 121° C / -40° F до +250° F (макс 125° C/257° F кратковрем)
<b>Маркировка</b>	Майларовая лента

**SEMPERIT**  FLEXLINE 5000 DN19 3/4" WP 380 Bar 5510 PSI ISO 18752-CCT MSHA IC-8/17 .Q.. 

Номинальный Ø		Внутренний Ø	Оплетка Ø	Внешний Ø	Рабочее давление		Давление испытаний	Давление разрыва	Радиус изгиба	Вес
мм	дюйм				bar	psi				
10	3/8	9,9	17,7	20,2	380	5510	760	1520	65	0,70
12	1/2	13,0	20,6	22,9	380	5510	760	1520	90	0,85
16	5/8	16,4	24,2	26,5	380	5510	760	1520	100	1,04
19	3/4	19,5	27,9	30,5	380	5510	760	1520	120	1,43
25	1	26,0	35,4	37,5	350	5075	700	1400	150	2,20
32	1 1/4	32,5	42,3	44,7	350	5075	700	1400	280	2,58

Publication date: March 2016 - Subject to changes without notice

\*протестировано более чем на 500.000 циклов согласно ISO6803:2008

#### Important Notice:

This information and our technical advice - whether verbal, in writing or by way of trials - are given in good faith but without warranty. Our advice does not release you from the obligation to check its validity and to test our products as to their suitability for the intended processes and uses. The choice of the correct type of hose is very important for the proper and safe use in service. Check your or your customer's specific application accordingly and instruct on limits and dangers of product use accurately. Application, use and processing of our products or your products manufactured on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Check for operating safety regularly. In the event of damage, in particular to the hose cover, hoses must be replaced for safety reasons.

#### Caution/Danger:

Wrong product selection, installation or improper treatment (such as crushing, tearing, stretching, loading with impermissible media and bending radius lower than specified) of the hoses can result in damage or failure of the hose, (often also serious) material damage and personal injury.

**semperflex**   
**HYDRAULICS**

A MEMBER OF THE SEMPERIT-GROUP